


MS3102A14S-5
CONNECTOR



WIRING CODE

CONNECTOR PIN	WIRE COLOR	FUNCTION
A	GREEN	EXCITATION +
B	WHITE	SIGNAL +
C	BLACK	EXCITATION -
D	RED	SIGNAL -
E	* SHIELD	GROUND

* SHIELD FLOATING AT SENSOR

VARIETY OF ROLLERS AVAILABLE. U-/V- GROOVE AND WEB/FILM/TAPE CYLINDRICAL TO 2.50 DIA.

MATING CONNECTOR AND 10 FT. OF 4-COND. AWG 20 WITH OVERALL SHIELD AND JACKET INCLUDED.

MATERIAL PATH WRAP ANGLE 36° TO 45° TYPICAL ROLLER DIAMETER DEPENDENT

8-1/2" WIDE FACEPLATE
BLACK HARD ANODIZED ALUMINUM

TENSION RANGES TO 100 LBS

TMI Tension Measurement, Inc
Colorado, USA • Tension-Measurement.com
TEL (303) 465-1011 • FAX (303) 466-9761

**MPHB BASE MOUNT TENSION SENSOR
WITH 8-1/2" WIDE FACEPLATE**

PART NO:
MPHB8-SERIES

MATERIAL:
ALUMINUM

TOLERANCES UNLESS OTHERWISE SPECIFIED:
U.S.O.
1 PLC. DEC. ±.030
2 PLC. DEC. ±.015
3 PLC. DEC. ±.005
ANGULAR ± 30"

SCALE: 1 = 2
DATE: 5-2002
BY: TMI